

TEE CAPACITY COMPARISON

	GPM
0.5 FT/SEC MAX MAX SLOT VELOCITY	58% OPEN AREA
	0.125 SLOT WIDTH

TEE SIZE	STANDARD	MAX-CAP	ULTRA-CAP
6 5/8	204.8	217.3	325.9
8 5/8	347.1	368.3	552.4
10 3/4	539.3	572.1	858.1
12 3/4	758.6	804.8	1207.1
16	1194.6	1267.3	1901.0
18	1511.9	1603.9	2405.9
21	2057.9	2183.1	3274.7
24	2687.8	2851.4	4277.2
27	3401.8	3608.9	5413.3
30	4199.8	4455.4	6683.1
33	5081.7	5391.0	8086.5
36	6047.6	6415.8	9623.6
42	8231.5	8732.6	13098.8
48	10751.4	11405.8	17108.7
54	13607.2	14435.5	21653.2
60	16799.0	17821.5	26732.3
66	20326.8	21564.1	32346.1
72	24190.6	25663.0	38494.5
78	28390.3	30118.4	45177.6
84	32926.0	34930.2	52395.4
96	43005.4	45623.2	68434.8

STANDARD=INTAKE TEE WITH FLOW COLLECTOR

MAX-CAP = INTAKE TEE WITH CORE TUBE

ULTRA-CAP = INTAKE TEE WITH CT & STRETCHED